Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the

application.

Please amend claims 1, 8, 29 and 34 as indicated below (material to be inserted

is in bold and underline, material to be deleted is in strikeout or (if the deletion is of five

or fewer consecutive characters or would be difficult to see) in double brackets [[]]):

**Listing of Claims:** 

1. (Currently Amended) A method of controlling a dissolution rate of a

bioactive agent, the method comprising:

identifying a target dissolution rate;

applying a first drop of solution carrying the bioactive agent at a first selected

location on a delivery substrate; and

positioning a second drop of solution carrying the bioactive agent at a second

selected location on the delivery substrate, wherein the location of the first drop and the

location of the second drop are selected based on [[a]] the target dissolution rate.

2. (Original) The method of claim 1, wherein the first drop and the second

drop at least partially overlap.

3. (Previously Presented) The method of claim 1, wherein the first drop and

the second drop are spaced sufficiently to avoid coalescing.

Page 2 -

AMENDMENT ACCOMPANYING REQUEST ...

Serial No. 10/801,381

HP Docket No. 200401494-1

KH Docket No. HPCC 3C7

- 4. (Original) The method of claim 1, wherein applying the first drop of solution and positioning the second drop of solution includes heating solution carrying the bioactive agent with a thermal ejection element.
- 5. (Original) The method of claim 4, wherein the heated solution is applied via at least two nozzles sized to eject drops of solution having substantially the same volume.
- 6. (Original) The method of claim 1, wherein applying the first drop of solution and positioning the second drop of solution includes displacing the solution carrying the bioactive agent with a piezoelectric ejection element.
- 7. (Original) The method of claim 6, wherein the displaced solution is applied via at least two nozzles sized to eject drops of solution having substantially the same volume.
- 8. (Currently Amended) The method of claim 1, further comprising positioning a plurality of drops of solution carrying the bioactive agent, each at a location selected based on [[a]] the identified target dissolution rate.
- 9. (Original) The method of claim 8, wherein a standard deviation of distance between adjacent drops is less than approximately 15% of a mean distance between adjacent drops.

Page 3 - AMENDMENT ACCOMPANYING REQUEST ...

Serial No. 10/801,381 HP Docket No. 200401494-1 KH Docket No. HPCC 3C7

The method of claim 8, wherein a standard deviation of -10. (Original) combined geometric surface area of overlapping drops is less than approximately 15% of a mean combined geometric surface area of overlapping drops.

KOLISCH#HARTWELL

- 11. (Cancelled)
- 12. (Cancelled)
- 13. (Cancelled)
- 14. (Cancelled)
  - 15. (Cancelled)
  - 16. (Cancelled)
  - 17. (Cancelled)
  - 18. (Cancelled)
  - 19. (Cancelled)
  - 20. (Cancelled)
  - 21. (Cancelled)
  - (Cancelled) 22.
  - 23. (Cancelled)
  - 24. (Cancelled)
  - 25. (Cancelled)
  - 26. (Cancelled)
  - 27. (Cancelled)
  - 28. (Cancelled)
- AMENDMENT ACCOMPANYING REQUEST ... Page 4 -Serial No. 10/801,381 HP Docket No. 200401494-1

KH Docket No. HPCC 3C7

29. (Currently Amended) A method of controlling a dissolution rate of a bioactive agent, the method comprising:

## identifying a target dissolution rate;

applying a first drop of solution carrying the bloactive agent at a first location on a delivery substrate;

selecting a second location on the delivery substrate for placement of a second drop of solution carrying the bioactive agent <u>from a plurality of possible second</u>

<u>locations</u>, the second location being selected in relation to the first location based on

[[a]] <u>the identified</u> target dissolution rate; and

positioning the second drop of solution at the selected second location on the delivery substrate.

- 30. (Previously Presented) The method of claim 29, wherein positioning the second drop effects a dot pattern with at least one dot at least partially overlapping with at least one other dot.
- 31. (Previously Presented) The method of claim 29, wherein positioning the second drop effects a dot pattern with at least one of the dot fully overlapping with at least one other dot.
- 32. (Previously Presented) The method of claim 29, wherein positioning the second drop effects a dot pattern with each dot discretely spaced from all other dots.
- 33. (Previously Presented) The method of claim 29, wherein the delivery substrate includes an ingestible media.

Page 5 - AMENDMENT ACCOMPANYING REQUEST ...
Serial No. 10/801,381
HP Docket No. 200401494-1
KH Docket No. HPCC 3C7

(Currently Amended) A method of controlling a dissolution rate of a 34. bioactive agent, the method comprising:

## Identifying a desired surface-to-mass ratio;

applying a first drop of solution carrying the bioactive agent at a first location on a delivery substrate;

selecting a second location on the delivery substrate for placement of a second drop of solution carrying the bioactive agent, the second location being selected to overlap the first location sufficiently to achieve [[a]] the Identified desired surface-tomass ratio of a resulting dot pattern; and

positioning the second drop of solution at the selected second location on the delivery substrate to achieve the resulting a dot pattern having the identified desired surface-to-mass ratio.

AMENDMENT ACCOMPANYING REQUEST ... Page 6 -Serial No. 10/801,381

HP Docket No. 200401494-1 KH Docket No. HPCC 3C7